



Sicilgesso Spa SS 113 KM 335,700 - Alcamo Diramazione - 91013 Calatafimi Segesta (TP) IT
T +39 0924 505446 - F +39 0924 505449 - sicilgesso@sicilgesso.it - www.sicilgesso.it
CF/P.IVA 00060760816 - CCIAA Trapani n. 37956 - Registro Imprese Trapani n. 1547 - Cap. soc. €837.000 i.v

DECLARATION OF PERFORMANCE

N° DoP- ADHESIO GOLD BIANCO-01

- Unique identification code of the product-type:** ADHESIO GOLD BIANCO
- Intended use/es:** improved cementitious adhesive with reduced slip and extended open time (C2TE) for all internal and external wall and floor tiling.
- Manufacturer:** Sicilgesso Spa (MGI Group) SS 113 KM 335,700 Alcamo Diramazione, 91013 Calatafimi Segesta (TP) Tel +39-0924-505446 Fax +39-0924-505449 www.sicilgesso.it - sicilgesso@sicilgesso.it
- System/s of AVCP:** System 3
- Harmonised standard:** UNI EN 12004-1:2017, already previous UNI EN 12004: 2012
Notified body/ies: The notified laboratory GEOLAB Srl n. 1307, performed the determination of product-type on the basis of type testing under system 3 and issued test report n. 51008 of 06/06/2016.
- Declared performance/s:**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	Class E	UNI EN 12004-1:2017
Initial tensile adhesion strength	≥1 N/mm ²	
Tensile adhesion strength after heat ageing	≥1 N/mm ²	
Tensile adhesion strength after water immersion	≥1 N/mm ²	
Tensile adhesion strength after freeze-thaw cycles	≥1 N/mm ²	
Extended open time (E): tensile adhesion strength	≥0.5 N/mm ² after not more than 30min	
Slip (T)	≤0.5 mm	
Release of dangerous substances	See SDS	

- Appropriate Technical Documentation and/or Specific Technical Documentation:** Reaction to fire performance declared without the need for further testing based on Commission Decision 2010/81/EC. Organic content <20% in weight and maximum layer thickness 20 mm.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Chief Executive Officer
Eng. Marzio Bresciani

At Calatafimi Segesta



on 15/07/2021



Sicilgesso®
GESSO. MALTE TECNICHE.

A COMPANY OF
mgigroup
SINCE 1948

Sicilgesso Spa SS 113 KM 335,700 - Alcamo Diramazione - 91013 Calatafimi Segesta (TP) IT
T +39 0924 505446 - F +39 0924 505449 - sicilgesso@sicilgesso.it - www.sicilgesso.it
CF/P.IVA 00060760816 - CCIAA Trapani n. 37956 - Registro Imprese Trapani n. 1547 - Cap. soc. €837.000 i.v

	 Sicilgesso® GESSO. MALTE TECNICHE. Gruppo MGI SS 113 KM 335,700 Alcamo Diramazione, 91013 Calatafimi Segesta (TP) Tel +39-0924-505446 Fax +39-0924-505449 www.sicilgesso.it - sicilgesso@sicilgesso.it
N° DoP- ADHESIO GOLD BIANCO-01 ADHESIO GOLD BIANCO 21 UNI EN 12004-1:2017 Improved cementitious adhesive with reduced slip and extended open time (C2TE)	
Reaction to fire	Class E
Initial tensile adhesion strength	≥1 N/mm ²
Tensile adhesion strength after heat ageing	≥1 N/mm ²
Tensile adhesion strength after water immersion	≥1 N/mm ²
Tensile adhesion strength after freeze-thaw cycles	≥1 N/mm ²
Extended open time (E): tensile adhesion strength	≥0.5 N/mm ² after not more than 30min
Slip (T)	≤0.5 mm
Release of dangerous substances	See SDS

Sicilgesso provides this annex together with the DoP to facilitate the consultation of the CE marking by customers. The marking shown here may differ from that printed on the packaging due to:

- graphic reworkings,
- use of a different language,
- product already in stock at the time of the mark updating,
- printing errors.